HOLLAND STONETM





INTERLOCKING CONCRETE PAVEMENT SYSTEM (ICP)

DURABLE FLEXIBLE PAVEMENT SYSTEM

STYLE	CODE	DIMENSIONS	BANDS	CUBES
Holland Stone™ 4″ x 8″	4HS	100mm x 200mm x 60mm Approximate 3 ⁷ /s" x ⁷⁷ /s" x 2 ³ /s" (PSF = 4.5 stones @ 28#)	15.7 SF 440# (72 stones)	94 SF 2640# (6 bands)
1 Inch Holland Stone™ 4″ x 8″	4HV100mm x 200mm x 25mm Approximate 37/s" x 77/s" x 1" (PSF = 4.5 stones @ 14#) Note: 1"Holland is suitable for veneers on pedestrian applications only.		N/A	94 SF 1175# (432 pcs)

COMPOSITION & MANUFACTURE

Typical Cross Section of Concrete Paving Stone



Edge restraint detail provided based on application.

> Borgert Pavers

Bedding Sand 1" Thick (ASTM C33)

Compacted Aggregate Base Class 2 or Class 5 (Thickness depends on soil condition and application)

Prior to screeding the bedding sand, the base surface tolerance must not exceed +/-1/4 in.(+/-6mm) over a 10gt. (3m) straight edge.

Compacted Soil Subgrade

- Pavers exceed industry standards: 8,000 psi 5% absorption
- Meets or exceeds ASTM C-936 and freeze-thaw testing per section 8 of ASTM C-67
- Manufactured with type A aggregates
- Associated with a range of LEED credits
- ADA Compliant

Written detailed specification information is available, call or visit our website at borgertproducts.com.



MAIN OFFICE: 8646 Ridgewood Road | P.O. Box 39 | St. Joseph, MN 56374 | PHONE 320.363.4671 | FAX 320.363.8516 CHICAGO, IL: 326 Butterfield Road | North Aurora, IL 60542 MADISON, WI: 6402 Loftus Road | Madison, WI 53532 PERMANENT OUTDOOR DISPLAY: MN State Fair Grounds | East Side of Underwood St. | Between Lee & Randall Avenues 0184020

HOLLAND STONETM






INTERLOCKING CONCRETE PAVEMENT SYSTEM (ICP)

BENEFITS OF ICP -

LAYING PATTERNS -


- Flexible system, does not crack or heave in cold climates
- Easier maintenance to the pavement and utilities underneath
- Achieve endless design possibilities with different shapes, textures, colors and laying patterns
- Use pavers to delineate lines and spaces to eliminate the need to maintain paint
- Suitable for a range of applications: plazas, walkways, driveways, roads, etc.
- Borgert pavers are made with granite, creating a dense, resistant wearing course



		1	
			[
_			

					Ь	- H
					Γ.	Г
						L
						_ L
	\vdash	Ч				
ļ	-	-		1		


(B) Basket Weave



F	Ι			П-
F	Τ	Ι		
\vdash				
Ι			Τ	

(A) Running Bond







(C) Herringbone 90°


(D) Framed Parquet

(E) Running Parquet






(G) Running Bond 45° (H) Basket Weave 45° (I) Herringbone 45°



(J) Offset Parquet



(K) Balance Parquet

(F) Basket Weave - 2