



HOLLAND SERIES™ NON-STOCK



INTERLOCKING CONCRETE PAVEMENT SYSTEM (ICP)

DURABLE FLEXIBLE PAVEMENT SYSTEM

STYLE		CODE	DIMENSIONS	CUBES
Double Holland™ 8" x 8" <i>*NOT SOLD BY THE BAND</i>		4DH	200mm x 200mm x 60mm Approximate 7 ⁷ / ₈ " x 7 ⁷ / ₈ " x 2 ³ / ₈ " (PSF = 2.25 stones @ 28#)	94 SF 2632# (216 pcs)
Holland Stone Square™ 12" x 12" <i>*NOT SOLD BY THE BAND</i>		4HQ	300mm x 300mm x 60mm Approximate 11 ⁷ / ₈ " x 11 ⁷ / ₈ " x 2 ³ / ₈ " (PSF = 1 Stone @ 28#)	112 SF 3136# (112 pcs)
Holland II™ 4" x 8" <i>*NOT SOLD BY THE BAND</i>			100mm x 200mm Approximate 3 ⁷ / ₈ " x 7 ⁷ / ₈ " (PSF = 4.5 stones @ 28#)	4HT - 60mm Height 94 SF 2632# (432 pcs) 4HT8 - 80mm Height 64 SF 2272# (288 pcs)
Holland Stone™ - 70mm 4" x 8" <i>*NOT SOLD BY THE BAND</i>		4H7	100mm x 200mm x 70mm Approximate 3 ⁷ / ₈ " x 7 ⁷ / ₈ " x 2 ³ / ₄ " (PSF = 4.5 stones @ 32.5#)	80 SF 2600# (360 pcs)

BENEFITS OF ICP

- Flexible system, does not crack or heave in cold climates
- Easier maintenance to the pavement and utilities underneath
- Achieve endless design possibilities with different shapes, textures, colors and laying patterns
- Use pavers to delineate lines and spaces to eliminate the need to maintain paint
- Suitable for a range of applications: plazas, walkways, driveways, roads, etc.
- Borgert pavers are made with granite, creating a dense, resistant wearing course



INTERLOCKING CONCRETE PAVEMENT SYSTEM (ICP)

COMPOSITION & MANUFACTURE

Typical Cross Section of Concrete Paving Stone



- > **Borgert Pavers**
- > **Bedding Sand 1" Thick (ASTM C33)**
- > **Compacted Aggregate Base Class 2 or Class 5**
(Thickness depends on soil condition and application)
- > **Compacted Soil Subgrade**

Prior to screeding the bedding sand, the base surface tolerance must not exceed +/-1/4 in. (+/-6mm) over a 10gt. (3m) straight edge.

Edge restraint detail provided based on application.

- Pavers exceed industry standards: 8,000 psi - 5% absorption
- Meets or exceeds ASTM C-936 and freeze-thaw testing per section 8 of ASTM C-67
- Manufactured with type A aggregates
- Associated with a range of LEED credits
- ADA Compliant

Written detailed specification information is available, call or visit our website at borgertproducts.com.

LAYING PATTERNS

